

4820

Cordless Area Imager



Features

Bluetooth® v1.2 Class 2 Radio reduces interference in existing RF backbones, including 802.11. Only v1.2 uses Adaptive Frequency Hopping (AFH) to mitigate data collisions in the 2.4GHz frequency band, while providing a 33 foot (10m) working range.

Smallest footprint in class, simplifying installation and conserving valuable counter space.

Optional presentation scanning while the imager is in its base for efficient, hands-free data capture.

Host-powered interface and RF link – an exclusive Hand Held Products feature that extends the mobile capabilities of the 4820 by drawing power from a portable device for radio and host communications.

Long lasting, field replaceable, high capacity lithium ion battery provides up to 50,000 scans per full charge with no conditioning required.

Solid state, no-moving-parts design withstands over 50 drops to concrete from 6 feet (1.8m).

Now Powered by New Adaptus™ Imaging Technology 5.0

The 4820 combines exclusive Adaptus™ Imaging Technology 5.0 with Bluetooth® wireless connectivity to provide a sleek, rugged cordless area imager for retail and commercial bar code reading.

The 4820 was purpose-optimized to help your enterprise improve productivity. In applications where operators must move about to read bar codes, cables become a limiting factor. These cumbersome cables lead to safety and ergonomic concerns, resulting in costly operational inefficiencies. With cordless bar code reading, users have the freedom of movement required to quickly, safely, and comfortably read bar code data within a 33 foot (10m) range.

Bar code reading is a mission-critical operation, which is why the 4820 cordless area imager was designed with an intensive focus on durability and reliability. With no moving parts and a robust housing, the 4820 will be available when needed, providing years of dependable service.

With our proven commitment to imaging innovation, we know what it takes to build world-class data capture solutions. Hand Held Products has over 15 years of experience developing, testing and deploying area imagers. To learn how the 4820 can make your business more efficient, call one of our locations listed on back, or visit us at www.handheld.com.

4820 Specifications

Performance

Illumination LEDs:	626nm ±30nm					
Aiming:	526nm ±30nm					
Green LED Aimer:	VGA, 752x480. Binary, TIFF, or JPEG output.					
Image:						
Working Range:						
4820 SR	8.3 mil Linear (.021cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil PDF417 (.038cm)	35 mil MaxiCode (.089cm)
Near	3.0 in. (7.6cm)	1.6 in. (4.1cm)	4.0 in. (10.2cm)	2.6 in. (6.6cm)	1.8 in. (4.6cm)	1.5 in. (3.8cm)
Far	7.1 in. (18.0cm)	12.7 in. (32.3cm)	5.7 in. (14.5cm)	8.5 in. (21.6cm)	9.7 in. (24.6cm)	12.5 in. (31.8cm)
4820SF	7.5 mil Linear (.019cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil Data Matrix (.038cm)	15 mil QR Code (.038cm)
Near	2.0 in. (5.1cm)	1.5 in. (3.8cm)	2.3 in. (5.8cm)	1.7 in. (4.3cm)	1.3 in. (3.3cm)	1.7 in. (4.3 cm)
Far	6.0 in. (15.2cm)	8.4 in. (21.3cm)	5.5 in. (14.0cm)	7.1 in. (18.0cm)	7.0 in. (17.8cm)	6.7 in. (17.0cm)
Pitch/Skew Angle:	±40°					
Motion Tolerance:	4 in. (10 cm) per second					

Radio

Frequency: 2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Bluetooth v. 1.2
Range: 33 ft. (10 m) typical
Data Rates: 720 KBps



Battery

Capacity: 1,800 mAh
Number of Scans: 50,000
Expected Hours of Operation: 16 hours
Charge Time at 9 Vac: 4 hours for full charge from full discharge

Symbologies

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite
Linear: Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS and Codablock
Postal: Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands Post)
OCR Fonts: OCR-A, OCR-B
Interfaces: Keyboard wedge, USB, TTL level RS-232, wand emulation, TTL level Serial Wedge, and IBM 46XX retail terminals.


Mechanical/Electrical

	4820 Scanner	2020 Base
Dimensions		
Weight:	9 oz. (255 g)	8.8 oz. (250 g) w/o cable
Height:	6.5 in. (16.5 cm)	3.1 in. (7.9 cm)
Power Requirements		
Input Voltage:	4.2 V internal battery	4.0 to 14 VDC (host) 8.5 to 9.5 VDC brick
Current Draw		125mA max @ 5V (no charging) 100 mA max @ 12V (no charging) 825mA max @ 12V (charging)
Environmental		
Sealing:	IP 41 (Water and Dust Resistant)	IP 41 (Water and Dust Resistant)
Temperature		
Operating:	32° to 122°F (0° to 50°C)	32° to 122°F (0° to 50°C)
Storage:	-40° to 140°F (-40° to 60°C)	-40° to 158°F (-40° to 70°C)
Humidity:	0 to 95%, non condensing	up to 95%, non condensing
Mechanical Shock:	Functional after 50 drops from 6 ft. (1.8 m)	Functional after 50 drops from 3.3 ft. (1 m)

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV, 2005 Sunrise Compliant

Laser Classification

Laser Aimer Model only: Class 2 under 21 CFR 1040.10 and 1040.11
1mW max output, 650 nm, EN60825-1: 1994+A11+A2



BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Hand Held Products.

Worldwide Offices

Offices Serving North America
 Skaneateles Falls, NY
 Tel: +1 315 685 8945
 or, in North America: +1 800 582 4263
 napresales@handheld.com
 Charlotte, NC
 Tel: +1 704 998 3998
 or, in North America: +1 800 582 4263
 napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
 Europe
 Tel: +31 (0) 40 29 01 600
 eupresales@handheld.com
 United Kingdom
 Tel: +44 (0) 1 925 240055
 eupresales@handheld.com
 Italy
 Tel: +39 (0) 2 67 100752
 eupresales@handheld.com

France
 Tel: +33 (0) 1 41 158220
 eupresales@handheld.com
Germany
 Tel: +49 (0) 7 477 151377
 eupresales@handheld.com
Spain
 Tel: +34 93 228 78 68
 eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
 Tel: +852 2511 3050
 appresales@handheld.com
Japan
 Tel: +813 5770 6312
 appresales@handheld.com
Shanghai
 Tel: +86 21 6361 3818
 appresales@handheld.com

Offices Serving Latin America
 Naples, Florida
 Tel: +1 239 263 7600
 lapresales@handheld.com
 São Paulo
 Tel: +55 11 2178 0500
 lapresales@handheld.com
 Rio De Janeiro
 Tel: +55 21 2178 0500
 lapresales@handheld.com
 Mexico
 Tel: +52 55 5203 2100
 lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2006. All rights reserved. Printed in the U.S.A.
 Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.