

MC9000-G Series

symbol
The Enterprise Mobility Company™

MOBILE COMPUTERS

Real-Time Mobile Computing Delivers Real Business Value

The MC9000-G Series from Symbol Technologies is an elegant, ruggedized mobile computer for use in bar code scanning-intensive applications throughout your enterprise. The MC9000-G gives your organization real-time access to mission-critical information from key points in your supply chain.

With a feature set that delivers superior data collection, communication and collaboration, the MC9000-G facilitates faster decision-making and increased productivity in a variety of environments—from the factory to the warehouse to the sales floor.

Market	Applications	Users
Manufacturing	Inventory management Supply-line replenishment Safety testing Parts tracking Maintenance/repair operations Shop floor communications Compliance verification Receiving/putaway/shipping	Assembly-line personnel Shipping/receiving personnel Shift supervisors Repair depot personnel
Retail	Warehouse management Price audits/changes Store receiving Inventory management Shrinkage control In-store communications	Sales associates Receiving-dock personnel Stock-room personnel Supervisors Merchandise managers Label printing staff
Wholesale Distribution	Warehouse management Returns processing EDI transactions Yard management	Warehouse personnel Loading-dock personnel Supervisors
Third-party Logistics	Warehouse management	Warehouse personnel

An Unprecedented Integration of Flexibility, Performance and Power

The MC9000-G Series takes your supply chain management to a new level of efficiency with exciting and versatile features. It gives you dynamic functionality, including long- and short-range variable laser scanning for all popular 1D bar codes, plus the optional imager supports a growing number of 2D symbologies. Robust memory (up to 64MB) and a powerful high-speed processor ensure maximum user productivity. And the unique torque-cell construction delivers unmatched ruggedness to perform in the toughest environments and to protect your investment.



Features	Benefits
Variable range scan engine	Allows short- (4 in./0.10 m) or long-range (40 ft./12.2 m) bar code scanning in one device
Extremely rugged design withstands multiple 6 ft. drops (1.8 m) to concrete; 2,000 1 m tumbles (4,000 hits)	Ensures less down time due to accidental drops
IP64 sealing rating (electronic enclosure)	Protects against water and dust to ensure reliable performance in rough conditions
Microsoft® Windows® CE .NET, Windows Mobile 2003 operating systems/terminal emulation software	Gives versatility through familiar interfaces with wide software application support
Intel® XScale™ PXA255 processor at 400 MHz	Delivers high-speed CPU performance for robust enterprise applications, including multimedia
3.8" large, bright, color display with backlit keypad	Allows easy viewing in many environments, such as ambient light
RS232/USB client or wireless LAN communications	Enables real-time data exchange for maximum productivity
Modular 43- and 53-key field-replaceable keyboard options	Provides multiple modes of data entry for maximum efficiency
Forward scanning, pistol grip ergonomics	Reduces user fatigue in scan-intensive applications

Unlock the Value of Your Information with End-to-End Mobility

End-to-end mobility solutions for the supply chain go beyond mobile devices and wireless connectivity. Symbol Enterprise Mobility Services was designed to ensure that every aspect of your mobility solution works seamlessly and at maximum efficiency.

For more information on the MC9000-G and its full line of accessories, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at: www.symbol.com/mc9000-g

MC9000-G Series Specification Highlights

Physical and Environmental Characteristics

Dimensions:	9.2 in. L x 3.6 in. W x 7.6 in. H
Weight:	26 oz. (includes battery, scanner and radio)
Keyboard:	43- and 53- key Terminal emulation (5250, 3270, VT)
Display:	
Embedded CE models:	3.8 in. 1/4 VGA Mono or Color
Windows Mobile models:	3.8 in. 1/4 VGA Mono or Color
Power:	Removable, rechargeable 7.4 volt 2200 mAh Li Ion battery pack (2200mAh, 7.4V)

Performance Characteristics

CPU:	XScale PXA255 processor at 400 MHz
Operating System:	Microsoft Windows Embedded CE. NET or Windows Mobile 2003
Memory:	Embedded CE: 32/32 MB or 64/64 MB Windows Mobile: 64/64 MB
Application Development:	SDK available through Symbol Developer Zone Web site
Data Capture Options:	1D scan engine Omni-directional 1D and 2D imaging engine

User Environment

Operating Temperature:	Monochrome/Color: -4° to 122° F (-20° to 50°C)
Storage Temperature:	-25° to 160° F (-40° to 70° C)
Humidity:	5% to 95% non condensing
Drop Spec:	Multiple drops to concrete: 6 ft: -10° C to 50° C 5 ft: -25° C to -10° C
Tumble:	2,000 one-meter tumbles at room temperature (4,000 hits)
Environmental Sealing:	IP64 (electronic enclosure)
ESD:	+/-15kVdc air discharge +/-8kVdc direct discharge, +/-8kVdc indirect discharge

Wireless Data Communications

WLAN:	Symbol Spectrum24, 802.11b, 802.11
Output Power:	100 mW U.S. and international
Data Rate:	802.11b: 11 MB per second 802.11: 2 MB per second
Antenna:	Internal
Frequency Range:	Country-dependent; typically 2.4 to 2.5 GHz
Bluetooth Support:	Optional

Peripherals and Accessories

Cradles:	Single-slot and 4-slot cradles available
Printers:	Supports extensive line of Symbol-approved printers, cables and accessories
Charger:	4-Slot universal battery charger
Other Accessories:	Cable adapter module; snap-on magnetic stripe reader and modem; full set of holsters

Regulatory

Electrical Safety:	Certified to UL60950, CSA C22.2 No. 60950, EN60950/IEC 950
EMI/RFI Radio Versions:	North America: FCC Part 2 (SAR), FCC Part 15 RSS210 Class B, EN 301 489-1, 489-17
EMI/RFI Batch Versions:	EU: EN55022 Class B EN55024 Japan: CISPR 22, Class B Australia: AS3548 North America: FCC Part 15, ICES 003 Class B
Laser Safety:	IEC Class2/FDA Class II in accordance with IEC60825-1/EN60825-1

EN410 CE



Specifications are subject to change without notice. Symbol® is the registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

NOTICE: Repairs of this product may require the use of Symbol proprietary parts (and/or Symbol proprietary information). Symbol will sell these parts (and provide this proprietary information) only to end-user customers for self-service. It is Symbol's policy not to sell these parts to third-party service providers and not to allow a third-party service provider to act as an ordering or receiving agent for the parts necessary to repair this product.

Corporate Headquarters
Symbol Technologies, Inc.
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722.6234/+1.631.738.2400
FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
(Singapore Branch)
Asia Pacific Division
230 Victoria Street #05-07/09
Bugis Junction Office Tower
Singapore 188024
TEL: +65.6796.9600
FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
EMEA Division
Symbol Place, Winnersh Triangle
Berkshire, England RG41 5TP
TEL: +44.118.9457000
FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
The Americas
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722.6234/+1.631.738.2400
FAX: +1.631.738.5990

Symbol Website
For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com
Or contact our pre-sales team at:
www.symbol.com/sales



MC9000G 0704

Part No. MC9000G Printed in USA 07/04 © Copyright 2004 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply.

symbol
The Enterprise Mobility Company™