

Falcon[®] 4410/4420

Portable Data Collection Terminals



Falcon 4420

Falcon 4410

Features:

- Intel[®] XScale™ PXA255 400MHz
- Windows CE .NET Operating System
- Standard, Long Range, Advanced Long Range Integrated Laser Scanner Options
- Industry Leading Beeper Volume of 84dB
- Instant-On Trigger (Falcon 4420 Only)
- Open architecture – PC Card Slot for RF Memory, etc.
- Supports leading 802.11b wireless LANs, including Cisco Aironet, Lucent/Proxim Orinoco, Symbol Spectrum24 HighRate

The Falcon 4410 and 4420 package the power of the latest mobile computing technology in a rugged and ergonomic mobile computer designed to master your inventory management applications. Whether in the harsh environment of a distribution center or in a fast-paced retail-in-store environment, the Falcon 4410/4420 has the feature set, accessories, and tools to meet your needs.

Built for the Warehouse

The Falcon 4410 and 4420 were designed to excel in warehouse and distribution center environments. Coupled with the widest range of scanning options (Standard, Long Range, and Advanced Long Range), low operating temperature specification (-20C), and an 84dB speaker, the Falcon 4410/4420 meets the unique needs of these industrial environments.

With a multiple 4-foot drop specification and an IP54 environmental seal rating, the Falcon 4410/4420 is well suited to withstand the rigors of your commercial or industrial environment.

Cutting Edge Mobile Technology

Inside the sleek Falcon 4410/4420 are cutting edge technologies from the leaders in mobile and wireless technology, such as Microsoft, Intel, Cisco, and others. The Falcon 4410/4420 features the Intel[®] XScale™ PXA255 400MHz processor and the Microsoft™ Windows CE .NET operating system, providing you with the power and flexibility to deploy sophisticated mobile applications in your enterprise.

The Intel XScale processor provides you with the highest performing mobile processor available today along with advanced power management capabilities for extended battery life. Microsoft's Windows CE .NET operating system gives you the freedom to select the software solution that best meets your needs.

Ergonomic Scanning

The Falcon 4410 is contoured to fit comfortably in an operator's hand for extended periods of fatigue-free data collection activities. The Falcon 4420 with its integrated handle is ergonomically designed for scan-intensive applications. The Falcon 4420 also allows for greater scanning efficiency when used with either the Long Range or Advanced Long Range laser, especially when scanning pallet labels on the top rack shelf.



Specifications

Falcon® 4410/4420

Mechanical

Dimensions

Length: 8.9" / 22.6 cm
 Width at display: 3.4" / 8.6 cm
 Width at grip: 2.5" / 6.4 cm
 Height at grip: 1.6" / 4.1 cm

Weight (w/battery pack)

4410, Laser, no radio: 17.6 oz / 499 g
 4420, Laser, no radio: 19.4 oz / 550 g
 4410, Laser, radio: 18.9 oz / 536 g
 4420, Laser, radio: 20.7 oz / 587 g

Display

3.3" diagonal VGA display;
 320 x 240 pixels;
 256-Level grayscale

Keypad

26-key standard alphanumeric - multi-click alpha characters,
 5 dedicated function keys, 5 shifted, navigation rocker
 52-key full alphanumeric
 5 dedicated function keys, 15 shifted, Navigation rocker
 5250 support

Construction

Industrial, high-strength polycarbonate/
 ABS-blend plastic

Environmental

Temperature rating

Operating: -4° to 122° F / -20° to 50° C
 Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Shock: multiple 4.0" / 1.2m drops to concrete

Water & Dust: IEC529 rating IP54DW

Optical

Light source:

Laser: 650nm

Scan rate:

1D: 35 ± 5 scans/sec.

Depth of Field: Refer to chart below

Indicators: Good read LED; scan LED

Ambient light immunity

Standard

Artificial light: 450 ft-candles /4,844 lux
 Sunlight: 8,000 ft-candles /86,112 lux

Range/Advanced Long Range

Artificial light: 450 ft-candles /4,844 lux
 Sunlight: 8,000 ft-candles /86,112 lux

Decoding Capability (autodiscriminates between)

ID Scan Engine

UPC A, E / EAN 8, 13
 EAN 128
 Code 128
 Code 93
 Interleaved 2 of 5
 Standard 2 of 5
 Code 39
 Code 39 Full ASCII
 Code 32
 Codabar
 MSI / Plessey

Safety and Regulatory

Electrical: Complies to CE

Emissions: FCC Part 15 - Class A, CISPR B

Laser classification: CDRH Class II;

(CAUTION: Laser Radiation - do not stare into beam);
 IEC 60825 Class 2



Printing resolution, contrast and ambient light dependent; *Minimum distance determined by symbol length and scan angle

Label Density	Standard Range	Long Range	Advanced Long Range
5 mil	3.0" - 5.0" / 8.0 - 13.0 cm		
7.5 mil	2.5" - 9.0" / 6.0 - 23.0 cm		
10 mil	2.5" - 13.0" / 6.0 - 33.0 cm	9.0" - 22.0" / 23.0 - 56.0 cm	
100% UPC / 13 mil			19.0" - 29.0" / 48.0 - 74.0 cm
15 mil	2.5" - 19.0" / 6.0 - 48.0 cm	7.0" - 38.0" / 18.0 - 96.0 cm	20.0" - 50.0" / 51.0 - 127.0 cm
20 mil	* - 21.0" / 6.0 - 53.0 cm	7.0" - 45.0" / 18.0 - 114.0 cm	
30 mil			33.0" - 98.0" / 84.0 - 249.0 cm
40 mil	* - 30.0" / 6.0 - 76.0 cm	10.0" - 90.0" / 25.0 - 229.0 cm	
55 mil	* - 36.0" / 6.0 - 91.0 cm	10.0" - 100.0" / 25.0 - 250.0 cm	27.0" - 109.0" / 69.0 - 277.0 cm
70 mil (reflective)		62.0" - 240.0" / 152.0 - 457.0 cm	114.0" - 250.0" / 290.0 - 635.0 cm
100 mil (reflective)		60.0" - 240.0" / 152.0 - 610.0 cm	125.0" - 360.0" / 318.0 - 914.0 cm

PSC Inc.

959 Terry Street
 Eugene OR 97402-9150 USA
 Tel: 800 695 5700 or 541 683 5700
 Fax: 541 345 7140

These product Specifications are subject to change without notice. Additional information concerning this product or other PSC products and services can be found at the PSC website, www.pscnet.com or contact your PSC representative for more information



PSC Worldwide Sales and Service locations

Australia Tel: 61 2 9878 8999
 Belgium Tel: 32 2 414 74 09
 Fax: 61 2 9878 8688 Fax: 32 2 410 11 63

Brazil/Chile Tel: 55 11 5507 7721
 Fax: 55 11 5507 7696

China Tel: 562-339-7000
 Fax: 562-339-7985

China - South Tel: 86 10 6857 9048
 Fax: 86 10 6857 8699

France Tel: 86 20 8765 9955
 Fax: 86 20 8765 9955

Germany Tel: 33 1 64 86 71 00
 Fax: 33 1 64 46 72 44

Tel: 49 6151 93580
 Fax: 49 6151 935858

Hong Kong Tel: 852 25846210
 Fax: 852 25210291

India Tel: 91 11 464 1662
 Fax: 91 11 464 1662

Italy Tel: 39 039 629031
 Fax: 39 039 6859496

Japan Tel: 81 3 3491 6761
 Fax: 81 3 3491 6656

Latin America Tel: 1 305 539 0111
 Fax: 1 305 539 0206

Singapore Tel: 65 435 1311
 Fax: 65 226 1242

Spain Tel: 34 91 203 65 00
 Fax: 34 91 203 65 01

Sweden Tel: 46 4010 84 92
 Fax: 46 4010 84 91

Turkey Tel: 90 212 23691 15
 Fax: 90 212 23691 16

United Kingdom Tel: 44 1923 809500
 Fax: 44 1923 809505

Part No. R40-0038-US B 0503

PSC and Falcon are registered trademarks; the PSC logo and RF Builder are trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners.

Printed in U.S.A.